

CS 740/CS 700 Speed Dome Camera

Features:

- 35X or 22X Optical Zoom, 16X Digital Zoom
- Day & Night (CS740) option: IR-Cut Filter Removable, ICR
- On Screen Display (OSD) Set-Up Menu
- 128 Present Points
- Remote Control via RS-485 (by CS-K60 Control Keyboard)
- IP66 for Outdoor, Built-in Heater & Fan (CS740)
- Wall / Pendant /Corner Mount for Choice



Specifications:

Model Type		CS 740	CS700
Image Device		¼" Color Sony Ex-View HAD (Hi-Res.)	¼" Color Sony Super HAD (Hi-Res.)
Picture Elements		NTSC:768x494, Pal:752x582	NTSC:768x494, Pal:752x582
Resolution		520TVL	480TVL
Min. Illumination		0.01 Lux (Night / BW) 0.5 Lux (Day / Color) /F1.6~3.7	0.7 Lux / F1.6
Electronic Shutter		NTSC: 1/60~1/30,000, PAL: 1/50~1/30,000	
Lens Furnished		35x (ICR) Auto Focus Zoom (3.6~12mm / F1.6~4.2)	22x Auto Focus Zoom (3.9~85.9mm / F1.6~3.7)
Digital Zoom Ratio		Basic 16 (Total Zoom Ratio 560x) 2x~16x Variable	Basic 16x (Total Zoom Ratio 352x) 2x~16x variable
Zoom Speed		8Sec	5 Sec
Focus Mode		Auto / Manual / Push Auto	
Iris Control		Auto / Manual	
White Balance		Auto / Hue / Indoor / Outdoor / Manual / Push / Auto	
Day & Night (ICR)		AE / Sensor / Day / Night	
Gain Control		Auto / Manual	
Back Light Comp.		On / Off	
Pan / Tilt Control	Angle Speed Dome	Pan: 360° , Tilt: 0°~90° Manual: Pan 1°~150° / sec, Tilt: 1°~100° / sec, Auto: Pan 1°~300° sec, Tilt: 1°~200° / sec	
Preset Point		128 Preset Points	
Sequence		6	
Remote Control		RS-485	
Protocol		PELCO D&P / LG	
On Screen Display		Set-Up Manu	
Auto Turn Around		Yes	
Alarm / Relay		6 / 1	
Sync. System		Internal	
Video Output		1 Vp-p / 75 Ohms	
Power Supply		DC 12V± 10% (option: AC24V)	
Power Consumption		DC: 2800mA max. / AC :2400mA max.	
Operation Temp.		-10°C ~ 50°C	