

CDN-575WS65

WDR Day/Night Ultra Low Light Long Range Vandal Dome Camera

Features:

- 1/3" SONY Super HAD CCD
- Long Range Vari-Focal Lens: 5~50mm
- Best WDR Performance, High Speed 5-level exposure
- Ultra Low Light 0.001 Lux
- Super High Resolution 650 TVL
- Built-in OSD function control
- Low Speed Shutter up to 32x
- Wide Dynamic Range 72dB at Dual Channel
- Dual Voltage: DC 12V / AC 24V
- Vandal Resistance



Specifications:

Model Type	CDN-575WS65
H. / V. Sync Frequency	15.734KHz / 60 Hz
Picture Elements	768 H x 494 V
Pick Up Device/ Image Sensor	1/3 type digital image device with WDR / SONY Super HAD CCD
Synchronization	AC: Line Lock, DC Internal
Scanning System	Interlaced
Electronic Shutter	1/60~1/120,000
Main Video Output	1.0 Vp-p Composite, 75 ohm
Day / Night	Normal Image, D/N with digital slow shutter
Horizontal Resolution	650TV Lines
Min. Illumination	0.15 Lux (Color), 0.03 Lux (B/W), 0.001 Lux (Sense Up)
S/N Ratio	48dB
Wide Dynamic	High Speed, Automatic 5-level exposure for each pixel
Dynamic Range	More than 72dB at Dual Channel
Gain Control	High/ Medium/ Custom/ Low
Auto White Balance Range	Single-push and manual, 2000K~11000K
Lens Options (DC Auto Iris)	Vari-Focal Lens : 5~50mm
Camera Control & Set Up	OSD Menu
Slow Shutter	Off, x2, x4, x8, x16, x32
Power Consumption	240mA at DC 12V / 3W at AC 24V
Power Requirement	DC 12V / AC 24V Dual Voltage
Operating Temperature	14° F ~ 122° F
Operating Humidity	Within 90% RH
Weight	2.8 lb
Dimension (in)	5 Ø x 5.5 (H) in