

CDN-3100W65

WDR Day/Night Ultra Low Light Box Camera

Features:

- 1/3" SONY Super HAD CCD
- High Speed 5-level exposure best WDR Performance
- Ultra Low 0.001 Lux
- Built-in OSD function control
- Low Speed Shutter up to 32x
- Wide Dynamic Range 120 dB Max
- Super High Resolution 650 TVL
- Dual Voltage: DC 12V / AC 24V



Specifications:

Model Type	CDN-3100W65
H. / V. Sync Frequency	15.734KHz / 60 Hz
Picture Elements	768 H x 494 V
Pick Up Device/ Image Sensor	1/3 type digital image device with WDR / SONY Super HAD CCD
Synchronization	AC: Line Lock, DC Internal
Scanning System	Interlaced
Mount Lens	C or CS mount
Main Video Output	1.0 Vp-p Composite, 75 ohm
Day / Night	Normal Image, D/N with digital slow shutter
Horizontal Resolution	650TV Lines
Min. Illumination	0.15 Lux (Color), 0.03 Lux (B/W), 0.001 Lux(Sense Up)
S/N Ratio	48dB
Wide Dynamic	High Speed, Automatic 5-level exposure for each pixel
Dynamic Range	120dB Max, 101 dB typical
Gain Control	High/ Medium/ Custom/ Low
Auto White Balance Range	Single-push and manual, 2000K~11000K
Back Light Compensation	OK / OFF Switchable
Camera Control & Set Up	OSD Menu
Slow Shutter	Off, x2, x4, x8, x16, x32
Power Consumption	160mA at DC 12V / 250mA at AC 24V
Power Requirement	DC 12V / AC 24V Dual Voltage
Operating Temperature	14° F ~ 122° F
Operating Humidity	Within 90% RH
Weight	1.15 lb
Dimension (in)	4.25x 3.25 x 3 in