

DH-IPC-HDW3200

2Megapixel IR Network Dome Camera



Features

- 1/3" 2Megapixel progressive scan Exmor CMOS
- H.264 & MJPEG dual-stream encoding
- Max 25/30fps@1080p
- DWDR, Day/Night(ICR), 2DNR, Auto iris, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- 3.3~12mm varifocal lens
- Built-in 1/1 alarm in/out
- Max IR LEDs length 20m
- Micro SD memory, PoE

PRODUCT SPECIFICATIONS

Technical Specifications

Model	DH-IPC-HDW3200P		DH-IPC-HDW3200N
Camera			
Image Sensor	1/3" 2Megapixel Exmor CMOS		
Effective Pixels	1920(H)x1080(V)		
Scanning System	Progressive		
Electronic Shutter Speed	Auto/Manual 1/3~1/10000	Auto/Manual 1/4~1/10000	
Min. Illumination	Color: 0. 1Lux/F1.2, B/W: 0.01Lux/F1.2; 0Lux/F1.2(IR on)		
S/N Ratio	>50dB		
Camera Features			
Max. IR LEDs Length	20m		
Day/Night	Auto(ICR)/Color/B/W		
Backlight Compensation	Off/BLC/HLC/DWDR		
White Balance	AUTO		
Gain Control	Auto/Manual		
Noise Reduction	2D		
Privacy Masking	Up to 4 areas		
Lens			
Focal Length	3.3-12mm		
Max Aperture	F1.4		
Focus Control	Manual		
Angle of View	H: 79.3°(Wide)~29.8°(Tele)		
Lens Type	Manual/Auto Iris (DC)		
Mount Type	Board-in Type		
Video			
Compression	H.264 / MJPEG		

PRODUCT SPECIFICATIONS

Resolution		1080P(1920×1080) / 720P(1280×720) / D1(704×576) / CIF(352×288)	/ 1080P(1920×1080) / 720P(1280×720) / D1(704×480) / CIF(352×240)
Frame Rate	Main Stream	1080P/720P(1 ~ 25/30fps)	
	Sub Stream	D1/CIF(1 ~ 25/30fps)	
Bit Rate		H.264: 32K ~ 8192Kbps, MJPEG: 32K ~ 20480Kbps	
Audio			
Compression		G.711a / G.711u (64kbps)/ PCM(128kbps)	
Interface		1/1 channel In/Out	
Network			
Ethernet		RJ-45 (10/100Base-T)	
Protocol		IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour	
ONVIF		ONVIF Ver. 2.0	
Max. User Access		10 users	
Smart Phone		iPhone, iPad, Android, Windows Phone	
Auxiliary Interface			
Memory Slot		Micro SD, Max 32GB	
Alarm		1/1 channel In/Out	
General			
Power Supply		DC12V, PoE(802.3af)	
Power Consumption		<6W	
Working Environment		-10℃~+60℃, 10%~90%	
Dimensions		Φ140.3x113.7mm	
Weight		0.8kg	

PRODUCT SPECIFICATIONS

Dimensions (mm)

