

PRODUCT SPECIFICATIONS

DH-HCVR5204/5208/5216A 4/8/16 All channel 720P 1U HDCVI DVR



Features

- Up to 4/8/16 cameras with 1080p realtime preview
- H.264 dual-stream video compression
- HCVR5204/5208/5216A: All channel 720P
- HDMI / VGA/BNC simultaneous video output
- 4/8 channel synchronous realtime playback, GRID interface & smart search
- 3D intelligent positioning with Dahua PTZ dome camera
- Support 2 SATA HDD up to 8TB, 2 USB2.0
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS

Technical Specifications

| Model | DH-HCVR5204A | DH-HCVR5208A | DH-HCVR5216A |
|------------------|---|----------------|-----------------|
| System | | | |
| Main Processor | Embedded processor | | |
| Operating System | Embedded LINUX | | |
| Video | | | |
| Input | 4 channel, BNC | 8 channel, BNC | 16 channel, BNC |
| Standard | NTSC(525Line, 60f/s), PAL(625Line, 50f/s) | | |
| Audio | | | |
| Input | 4 channel, BNC | | |

PRODUCT SPECIFICATIONS

| | | | |
|----------------------------------|---|---------------------------------------|------------|
| Output | 1 channel,BNC | | |
| Two-way Talk | Reuse audio input/output channel 1 | | |
| Display | | | |
| Interface | 1 HDMI, 1 VGA,1 BNC | | |
| Resolution | 1920×1080, 1280×1024, 1280×720, 1024×768, 800×600 | | |
| Display Split | 1/4 | 1/4/8/9 | 1/4/8/9/16 |
| Privacy Masking | 4 rectangular zones (each camera) | | |
| OSD | Camera title, Time, Video loss, Camera lock, Motion detection, Recording | | |
| Recording | | | |
| Video/Audio Compression | H.264 / G.711 | | |
| Resolution | 720P(1280×720/1280×600)/960H(960×576/960×480)/D1/4CIF(704×576/704×480) / CIF(352×288/352×240) / QCIF(176×144/176×120) | | |
| Record Rate | Main Stream: | 720P/960H/D1/HD1/2CIF/CIF(1~25/30fps) | |
| | Extra Stream | CIF/QCIF(1~25/30fps) | |
| Bit Rate | 48~6144Kb/s | | |
| Record Mode | Manual, Schedule(Regular(Continuous), MD), Stop | | |
| Record Interval | 1~120 min (default: 60 min), Pre-record: 1~30 sec, Post-record: 10~300 sec | | |
| Video Detection&Alarm | | | |
| Trigger Events | Recording, PTZ, Tour, Video Push, Email, FTP, Spot, Buzzer & Screen tips | | |
| Video Detection | Motion Detection, MD Zones: 396(22×18), Video Loss & Camera Blank | | |
| Alarm Inuput | 4 channel | 8 channel | 16 channel |
| Alarm Output | 3 channel | | |
| Playback & Backup | | | |
| Sync Playback | 1/4 | 1/4/8 | 1/4/8/16 |
| Search Mode | Time/Date, MD & Exact search (accurate to second) | | |
| Playback Functions | Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom | | |
| Backup Mode | USB Device / Network | | |
| Network | | | |
| Ethernet | RJ-45 port (10/100M/1000M) | | |
| Network Functions | HTTP, IPv4/IPv6, TCP/IP, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter | | |
| Max. User Access | 128 users | | |
| Smart Phone | iPhone, iPad, Android, Windows Phone | | |
| Storage | | | |
| Internal HDD | 2 SATA port, up to 8TB | | |
| Auxiliary Interface | | | |
| USB Interface | 2 ports(1 Rear), USB2.0 | | |

PRODUCT SPECIFICATIONS

| | |
|---------------------|---|
| RS232 | 1 port, For PC communication & Keyboard |
| RS485 | 1 port, For PTZ control |
| General | |
| Power Supply | DC12V/5A |
| Power Consumption | 15W(without HDD) |
| Working Environment | -10 ~ +55°C / 10~90%RH / 86~106kpa |
| Dimension(W×D×H) | 1U, 375mm×285mm×45mm |
| Weight | 2.35KG(without HDD) |

System Connection

