

# PRODUCT SPECIFICATIONS

## DH-HAC-HDW2200S

### 2 Megapixel 1080P Water-Proof HDCVI Mini Dome Camera with IR



#### Features

- 1/3" 2Megapixel CMOS
- 25/30/fps@1080P, 25/30/50/60fps@720P
- Real-Time high speed long transmission up to 900 Feet
- HD and standard definition switchable
- OSD Menu, control over coaxial cable
- Day/Night (ICR), AWB, AGC, BLC, 3D-DNR,
- 6mm fixed lens (2.8mm, 3.6mm, 8mm optional)
- Max. IR LEDs length 60 feet, Smart IR
- IP66, DC12V

#### Technical Specifications

Model	DH-HAC-HDW2200SP	DH-HAC-HDW2200SN
Camera		

# PRODUCT SPECIFICATIONS

Image Sensor	1/3" 2 Megapixel CMOS
Effective Pixels	1920(H)x1080(V)
Electronic Shutter	1/3s~1/100,000s
Synchronization	Internal
Min. Illumination	0.05 Lux@F1.2(0Lux IR LED on)
Video Output	1-Channel BNC HDCVI high definition video output/CVBS standard definition video output (Can Switch)
<b>Camera Features</b>	
Max. IR LEDs Length	60 Feet, Smart IR
Day/Night	Auto(ICR)/B&W/Color
Noise Reduction	3D/2D
OSD Menu	Support
<b>Lens</b>	
Focal Length	3.6mm (2.8mm, 6mm 8mm optional)
Mount Type	M12
<b>General</b>	
Power Supply	DC12V±10%
Power Consumption	Max 3.5W
Working Environment	-30°C~+60°C / Less than 95%RH( no condensation)
Transmission Distance	Over 900 Feet via 75-3 coaxial cable
Ingress Protection	IP66
Dimensions	Φ113.6mm×85.8mm
Weight	300g

## Dimensions (mm)

