

# PRODUCT SPECIFICATIONS

## DH-HAC-HFW2200B

2 Megapixel 1080P Water-Proof HDCVI Bullet camera with IR



### Features

- 1/3" 2 Megapixel CMOS
- 25/30/fps@1080P, 25/30/50/60fps@720P
- Real-Time High Speed transmission up to 900 feet.
- HD and standard definition switchable.
- OSD Menu, control over coaxial cable
- Day/Night(ICR), AWB, AGC, BLC, 3D-DNR
- 6mm fixed lens (2.8, 3.6mm, 8mm optional)
- IR LEDs Length up to 90 feet, Smart IR technology.
- IP66, DC12V

# PRODUCT SPECIFICATIONS

## Technical Specifications

Model	DH-HAC-HFW2200BP		DH-HAC-HFW2200BN
Camera			
Image Sensor	1/3" 2 Megapixel CMOS		
Effective Pixels	1920(H)×1080(V)		
Electronic Shutter Speed	1/3s ~ 1/100,000s	1/3s ~ 1/100,000s	
Synchronization	Internal		
Video Frame Rate	1920x1080@25 fps 1920x1080@30 fps 1280x720@25 fps 1280x720@30 fps 1280x720@50 fps 1280x720@60 fps		
Min. Illumination	0.05Lux@F1.2(0Lux IR LED on)		
Video Output	1-channel BNC HDCVI high definition video output/ CVBS standard definition video output (Can switch)		
Camera Features			
Max. IR LEDs Length	90 Feet, Smart IR		
Day/Night	Auto(ICR)/Color/B/W		
Noise Reduction	3D/2D		
OSD Menu	Support		
Lens			
Focal Length	6mm (2.8 mm, 3.6mm, 8mm optional)		
Mount Type	M12		
General			
Power Supply	DC12V±10%		
Power Consumption	Max 6.5W		

# PRODUCT SPECIFICATIONS

Working Environment	-30°C~+60°C Humidity is less than 95%(no condensation)
Transmission Distance	Over 900 Feet via 75-3 coaxial cable
Ingress Protection	IP66
Dimensions(W×D×H)	200.2mm×89.1mm×80.4mm
Weight	450g

## Dimensions (mm)

