

Product Specifications

HAC-HDBW2220RN-Z

2.4Megapixel 1080P Vandal-proof IR HDCVI Dome Camera



Features

- 1/2.8" 2.4Megapixel CMOS
- 30@1080P, 30/60fps@720P
- High speed, long distance real-time transmission
- HD and standard definition switchable
- OSD Menu, control over coaxial cable
- Day/Night(ICR), AWB, AGC, BLC, 3D-DNR
- 2.7~12mm motorized lens
- Max. IR LEDs length 30m, Smart IR
- IP66, IK10, DC12V

Product Specifications

HAC-HDBW2220RN-Z

Technical Specifications

| | |
|------------------------|--|
| Model | HAC-HDBW2220RN-Z |
| Camera | |
| Image Sensor | 1/2.8" 2.4Megapixel CMOS |
| Effective Pixels | 1984(H)×1225(V) |
| Electronic Shutter | 1/3s~1/100,000s |
| Video Frame Rate | 30/60fps@720P; 30fps@1080P |
| Synchronization | Internal |
| Min. Illumination | 0.05Lux@F1.2(AGC ON), 0Lux IR on |
| Video Output | 1-channel BNC HDCVI high definition video output/ CVBS standard definition video output (Can switch) |
| Camera Features | |
| Max. IR LEDs Length | 30m, Smart IR |
| Day/Night | Auto(ICR) / Color / B/W |
| Noise Reduction | 2D/3D |
| OSD Menu | Support |
| Lens | |
| Focal Length | 2.7~12mm |
| Lens Type | Motorized / Fixed Iris |
| Mount Type | Φ14 |
| General | |
| Power Supply | DC12V±10% |
| Power Consumption | Max 9.6W |
| Working Environment | -30°C~+60°C / Less than 95%RH (no condensation) |
| Transmission Distance | Over 300m via 75-3 coaxial cable |
| Ingress Protection | IP66 & IK10 |
| Dimensions | Φ122mm×89mm |
| Weight | 0.45kg |

Product Specifications

HAC-HDBW2220RN-Z

Dimensions (mm)

