## **CCTV Product Specials**

IP CAMERA	Model	Specification
	HFW1200S-W	2 Mp Full HD Wi-Fi Network , Small IR-Bullet Camera ,3.6 mm Lens/ 72°, Wi-Fi(IEEE802.11b/g/n), DWDR, IR100FT , IP66, DC12V
0	HFW1000S	1 Mexapixel HD Network ,Weather-proof Small IR-Bullet Camera ,3.6 mm Lens/ 63.5°, IR 100FT,3D Noise Reduction,DWDR,IP66, PoE
0	HFW1320S	3 Mp Full HD Network , Mini IR Bullet Camera ,3.6 mm Lens/ 81°, IR 100FT,DWDR,3D Noise Reduction, Corridor Mode, IP67, PoE
	HFW4300E	3 Mp Full HD Network , Small IR-Bullet Camera , 3.6mm/ 72.5° Lens,IR 100FT,DWDR, IP66, PoE
	HFW4800E	4K Ultra HD Network Small IR-Bullet Camera, 4K(3480x 2160), 4 mm Lens/ 80°, IR 100FT,3D Noise Reduction,DWDR, IP66, PoE
	HDBW1000E	1 Mexapixel HD Network ,Vandal-proof Small IR Dome Camera ,2.8 mm Lens/ 89°, IR 100FT,3D Noise Reduction,DWDR, Micro SD,IP66, IK10, PoE
	HDW1200S	2 Megapixel HD Network IR Mini Dome Camera, 2.8 mm Lens/89.8°, DWDR, IR 100FT, IP66, PoE
	HDBW1300E	3Mexapixel HD Network , Vandal-proof Small IR DomeCamera, 2.8mmLens/89°, IR100FT, DWDR, Weather- proof IP66, IK10, PoE
	HDW4300FN-PT	3 Mp Full HD Network Mini PT Dome Camera ,3.6 mm Lens/72.5°,Max100°/sPresetSpeed180°Pan,90°Tilt,Micro SD,IP66,Vandal-proof,IK10
	HDBW4800E	4K Ultra HD Network Mini Dome Camera, 4K(3480x 2160),4mmLens/80°,IR66FT,3DNoiseReduction,DWDR,IP6 6,IK10,PoE
IP PTZ CAMERA	Model	Specification
PTZ	SD22204TN-GN	2MpHD,3X,OpticalZoom,LowLight,NetworkPTZ Dome,3~9mmLens,93°~31.7°,PelcoD/P,DWDR, 0.0005 Lux, Max 80°/s pan, Micro SD,IP66,PoE,DC12V
NVR	Model	Specification
	NVR4104W	4Channel Video, Wireless NVR up to 1HDD, HDMI, VGA output, WPS one-key add, Max 80Mbps bandwidth, 4 Ch realtime playback, Up to 5Mp resolution
	NVR4108H-P	8Channel Video,NVR up to 1HDD,with 4 ports PoE,HDMI,VGA output, Max 80 Mbps,8 Ch realtime playback Up to 5Mp resolution
PoE SWITCH	Model	Specification
	PFS3110-8P-96	8-Port PoE Switch,≤93W,two-layer Industrial wide temperatureDesign,1x1000base-X,1x10/100/1000base-T,8x10/100(PoEpower)